

Style A INTRIMIK® with Analog Indication - Inch Models



Features:

- INTRIMIK/IMICRO's measuring arms move at right angles to the spindle.
- Analog reading, with graduations as shown in the table.
- Instruments in the range .275" to 4.00" have hardened steel measuring points (770 HV).
- Instruments in the range 4.00" to 12.00" have tungsten carbide inserts in the measuring points (1300 HV).



DIN 863 T4
(style C1)
NF E 11-099

Models from
0.275 to 0.500 in
with vernier

Measuring faces
on models from
0.275 to 0.500 in:
hardened steel

0.50 to 4.0 in:
hardened steel

4 to 12 in:
tungsten carbide tipped

Single
instruments:
shipping box. Full sets:
plastic case or suitcase

Identification
number

Inspection
report with a
declaration of conformity

NO	EOP	NO	in	in	Measuring Depth (in) With Extensions		
					None	One	Two
599-281-3	43972	08.20001	.275 to .350	.0001	2	6	10
599-281-4	43974	08.20002	.350 to .425	.0001	2	6	10
599-281-5	43976	08.20003	.425 to .500	.0001	2	6	10
599-281-6	43978	08.20301	.500 to .600	.0002	3	9	15
599-281-7	43980	08.20302	.600 to .700	.0002	3	9	15
599-281-8	43982	08.20303	.700 to .800	.0002	3	9	15
599-281-10	43984	08.21101	.800 to 1.000	.0002	3	9	15
599-281-12	43986	08.21102	1.000 to 1.200	.0002	3	9	15
599-281-14	43988	08.21103	1.200 to 1.400	.0002	3	9	15
599-281-16	43990	08.21104	1.400 to 1.600	.0002	3	9	15
599-281-20	43992	08.21801	1.600 to 2.000	.0002	3	9	15
599-281-24	43994	08.21802	2.000 to 2.400	.0002	3	9	15
599-281-28	43996	08.21803	2.400 to 2.800	.0002	3	9	15
599-281-32	43998	08.21804	2.800 to 3.200	.0002	3	9	15
599-281-36	44000	08.21805	3.200 to 3.600	.0002	3	9	15
599-281-40	44002	08.21806	3.600 to 4.000	.0002	3	9	15
599-281-50	44004	08.22601	4.000 to 5.000	.0005	4	10	
599-281-60	44006	08.22602	5.000 to 6.000	.0005	4	10	
599-281-70	44008	08.22603	6.000 to 7.000	.0005	4	10	
599-281-80	44010	08.22604	7.000 to 8.000	.0005	4	10	
599-281-90 *	44012	08.23101 *	8.000 to 9.000	.0005	4	10	
599-281-100 *	44014	08.23102 *	9.000 to 10.00	.0005	4	10	
599-281-110 *	44016	08.23103 *	10.00 to 11.00	.0005	4	10	
599-281-120 *	44018	08.23104 *	11.00 to 12.00	.0005	4	10	

* Comes with 6" extension in finished wooden case