

MarCal. The new Generation with the Reference-System


WATERPROOF CALIPERS

► | The water-proof digital caliper **MarCal** 16 EWR, with protection class IP67 and the Reference Lock-Function, ensures both accurate and reliable results even in the most toughest workshop conditions. | ◀

The high-contrast display with 8.5 mm high digits enables accurate, fatigue free reading of the measurement results.



The **Reference-Lock-Function** prevents operating error caused by accidental usage of the operating buttons.




Universal SPC-interface (optional). You have a choice of **MarConnect** data outputs, select either **USB**, **Digimatic** or **Mahr Opto RS232**



Lapped measuring faces for accurate measurement.

The new Reference system is extremely energy efficient as when the caliper is in standby mode; almost no power is required, thus **extending the life of the battery to up to 50%.**



MarCal calipers have **lapped guide way surfaces**, these guarantee an even and sensitive run of the slide.

Surface of the guide way



Mahr


Lapped guide way

Code Initials	IP	International Protection
First digit	6	Dust-tight
Second digit	7	Protected against temporary immersion in water



Protection class **IP67** in accordance to IEC 60529, the water proof measuring system **FPS** (Fluid Protected measuring System) with a sealed housing.

Digital Caliper MarCal 16 EWR with data output



REFERENCE

Features

Functions:



- ON/OFF
- RESET (Set display to zero)
- mm/inch
- Reference-Lock/Unlock
- DATA (Data transmission via connection cable)
- Auto-ON/OFF
- Immediate measurement due to the Reference system


- Excellent resistance against dust, coolants and lubricants, protection class IP67
- MarConnect data output, choose alternatively: USB, OPTO RS232C or Digimatic
- Dirt wipers are integrated in the slide

- Life of the battery up to 3 years
- Max measuring speed 2.5 m/s (100"/s)
- High contrast LCD with 8.5 mm high digits
- Lapped guide way
- Slide and beam made of hardened stainless steel

- Measuring blades for inside measurement
- Step measuring function
- Locking screw
- Supplied with: Case, battery, operating instructions

Technical Data

Measuring range	Resolution	Error limit G	DIN 862	Depth rod		Friction wheel	Order no.
							
mm (inch)	mm / inch	mm / inch					
150 (6")	0.01/ .0005"	0.03/ .001"	●	●			4103064
150 (6")	0.01/ .0005"	0.03/ .001"	●		●		4103066
200 (8")	0.01/ .0005"	0.03/ .001"	●		●		4103068
300 (12")	0.01/ .0005"	0.04/ .0015"					4103070
150 (6")	0.01/ .0005"	0.03/ .001"	●	●		●	4103065
150 (6")	0.01/ .0005"	0.03/ .001"	●		●	●	4103067
200 (8")	0.01/ .0005"	0.03/ .001"	●		●	●	4103069
300 (12")	0.01/ .0005"	0.04/ .0015"				●	4103071



Dimensions


mm	a	b	c	d	e
150	10	40	16	235	16 x 3
200	10	50	19	285	16 x 3.5
300	14	64	19	388	16 x 4

Accessories


	Order no.	
Depth Measuring Bridge	16 Em	4102020
Battery 3V, Type CR 2032		4102520
Data Connection Cable USB (2 m)	16 EXu	4102357
Data Connection Cable Opto RS232C (2 m), with SUB-D jack 9-pin	16 EXr	4102410
Data Connection Cable Digimatic (2 m), Flat plug 10-pin	16 EXd	4102411

Accessories for Data Processing see Chapter 11

Digital Caliper MarCal 16 EWR special design



16 EWR-AR



16 EWR-NA







REFERENCE


Features

Features are the same as the MarCal 16 EWR, please refer to Page 1-6, additional features can be found in the Technical Data.


Technical Data

	Measuring range	Resolution	Error limit G	Depth rod	Order no.	Type
	mm (inch)	mm / inch	mm	 		
16 EWR-AR	200 (8")	0.01 / .0005"	0.03		4103082	Scribing/markings caliper
16 EWR-NA	150 (6")	0.01 / .0005"	0.03		4103074	Keyseat caliper

16 EWR-AR



16 EWR-NA



Accessories

Battery, Data Connection Cables see Page 1 - 6

Accessories for Data Processing see Chapter 11


MarCal - The innovative Reference-System

Just set once to zero


All Mahr digital calipers with this logo **REFERENCE** are equipped with the innovative Reference-System. The zero position just has to be set once: after setting the zero position, the zero remains stored for all further measurements. Therefore, once the caliper is switched ON or the slide is moved the caliper is immediately ready for measurement. The need to reset to zero with a conventional caliper once the caliper is switched on has now become obsolete.

Conventional


① Switch ON




② Close the measuring jaws



③ Set to zero




④ Results of measurement



REFERENCE - System


① Switch ON



Press the ON key or move the slide

REFERENCE

② Results of measurement



IP-Protection classes

First digit is the degree of protection according to IEC 60529

Protection against particles, contaminants and dust

0	Not protected
1	Particles > 50.0 mm
2	Particles > 12.5 mm
3	Particles > 2.5 mm
4	Particles > 1.0 mm
5	Dust protected
6	Dust tight

Second digit is the degree of protection according to IEC 60529 (approximate)

Protection against wet conditions (fluids)

0	Not protected
1	Falling water drops - vertical
2	Falling water drops - tilted < 15°
3	Spray water < 60°
4	Water splashing from all directions
5	Water jets from all directions
6	Powerful water jets
7	Temporary immersion in water
8	Continuous immersion in water



Example:
IP67 means that the product is "Dust tight" and is protected against "Temporary immersion in water".