

Dial Indicators

SERIES 0 - Compact type



1911



1923



1911



1913-10

SPECIFICATIONS

Inch Stem dia. 3/8", #4-48 UNF Thread ANSI/VGD type

Graduation	Range	Range/rev	Dial reading	Order No.		Accuracy		Measuring force	
				w/ lug	Flat-back	First 2.5 Rev	Overall Accuracy		
.0001"	.01"	.004"	0-2-0	1927-10	1927B-10	±.0002"	±.0002"	1.4N or less	✓
.0001"	.025"	.01"	0-5-0	1925-10	1925B-10	±.0002"	±.0002"	1.4N or less	✓
.0005"	.05"	.02"	0-10-0	1923	1923B	±.0005"	±.0005"	1.4N or less	—
.001"	.1"	.04"	0-20-0	1921	1921B	±.001"	±.001"	1.4N or less	—

Metric Stem ø 8mm, M2.5 x 0.45 Thread ISO/JIS type

Graduation	Range	Range/Rev	Dial reading	Order No.		Accuracy		Measuring force	
				w/ lug	Flat-back	First 2.5 Rev	Overall Accuracy		
0.002mm	0.5mm	0.2mm	0-100-0	1913-10	1913B-10	±0.011mm	±0.011mm	1.4N or less	✓
0.01mm	2.5mm	1mm	0-50-0	1911	1911B	±0.011mm	±0.011mm	1.4N or less	—

Jeweled bearing type

DIMENSIONS

Inch Model Unit: Inch

Order Number	A	B
1927-10	1.46"	.26"
1925-10	1.48"	.28"
1923	1.51"	.31"
1921	1.58"	.37"

Metric Model Unit: mm

Order Number	A	B
1911	42	11.5
1913-10	39.5	9