



224, 224M Series Interchangeable Anvil Micrometers

0-24" / 0-600mm

Unusual flexibility, plus a wide range of measurement makes the Starrett 224 series satin-chrome micrometers very popular in machine or automotive repair shops and for all applications requiring a versatile micrometer.

Each micrometer is equipped with a series of easily interchangeable anvils, thus providing the full range in steps of 1" or 25mm with a single micrometer. Suitable wrenches are furnished to make necessary adjustments.

These larger sizes have .300" (7.6mm) anvil and spindle diameters for ease of use on larger work.

Readability features

- Starrett satin chrome finish – no glare – resists rust
- Advanced sleeve design with staggered lines and distinct figures for precise and easy readability
- Large thimble diameter with distinct figures

Ease-of-Handling Features

- Balanced frame and thimble design ensure easy handling and better readability
- Ring-type knurled lock nut for quick and sure locking
- Combination ratchet and speeder for uniform pressure and quicker adjustment

Accuracy and Long-Life Features

- Rigid and stable special cast iron frame with appropriate perforations for lightness and ribbed for strength and stability
- Extremely hard and stable one-piece spindle (the heart of our accuracy)
- Interchangeable anvils
- Micro-lapped measuring faces
- Quick and easy sleeve adjustment



224, 224M Interchangeable Anvil Micrometers

Range	Graduation	With Ratchet Stop, Lock Nut, In Case		234 Standards Furnished
		Catalog No.	EDP	
0-4"	.001"	224AARLZ	50770	1", 2", 3"
2-6"		224ARLZ	50772	2", 3", 4", 5"
6-9"		224BRLZ	50774	6", 7", 8"
6-12"		224GRLZ	50776	6", 7", 8", 9", 10", 11"
9-12"		224CRLZ	50778	9", 10", 11"
12-16"		224DRLZ	50780	12", 13", 14", 15"
16-20"		224ERLZ	50782	16", 17", 18", 19"
20-24"		224JRLZ	50784	20", 21", 22", 23"
0-100mm	0.01mm	224MAARLZ	50771	25, 50, 75mm
50-150mm		224MARLZ	50773	50, 75, 100, 125mm
150-300mm		224MGRLZ	50777	150, 175, 200, 225, 250, 275mm
300-400mm		224MDRLZ	50781	300, 325, 350, 375mm
400-500mm		224MERLZ	50783	400, 425, 450, 475mm
500-600mm		224MJRLZ	50785	500, 525, 550, 575mm